

AB-1663 US
S.N. 09/850,367

CLAIM AMENDMENTS

The following is a complete listing of the pending claims:

Cancel claims 1 through 33.

34. (Previously Presented) A liquid crystal display (LCD) device, comprising:
a display unit configured to display an image;
a bottom chassis receiving the displaying unit;
a mold frame receiving the bottom chassis and having an opening exposing a bottom surface of the bottom chassis; and
a printed circuit board (PCB) configured to control the display unit and disposed outside the mold frame and directly on the bottom surface of the bottom chassis.

35. (Previously Presented) The LCD device of claim 34, further comprising a shield case covering the PCB.

36. (Previously Presented) The LCD device of claim 35, wherein the opening exposes a center portion of the bottom surface of the bottom chassis.

37. (Previously Presented) The LCD device of claim 36, wherein the PCB includes:
a power supply unit configured to supply power to the display unit; and
a signal converter unit configured to convert a signal provided to the display unit.

38. (Previously Presented) The LCD device of claim 34, further comprising a fixture unit that fixes the PCB to the bottom surface of the bottom chassis.

39. (Previously Presented) The LCD device of claim 38, wherein the PCB is arranged between the bottom chassis and the fixture unit.

AB-1663 US
S.N. 09/850,367

40. (Previously Presented) The LCD device of claim 39, wherein the PCB has one end overlapped with the fixture unit.

41. (Previously Presented) The LCD device of claim 38, wherein the fixture unit includes a bracket having a first end connected to the PCB and a second end connected to the bottom surface of the bottom chassis.

42. (Previously Presented) The LCD device of claim 41, wherein one or more elements is mounted on the PCB, wherein the fixture unit has a first average thickness, and wherein the first average thickness of the fixture unit is less than a height of the highest one of the one or more elements mounted on the PCB.

Cancel claims 43 through 49.

50. (Previously Presented) A monitor, comprising:
a front case;
a rear case combined with the front case; and
a liquid crystal display (LCD) device disposed between the front case and rear case and comprising:
a display unit;
a bottom chassis receiving the display unit;
a mold frame receiving the chassis and having an opening exposing a bottom surface of the bottom chassis; and
a printed circuit board (PCB) configured to control the display unit and disposed outside the mold frame and directly on the bottom surface of the bottom chassis.

51. (Previously Presented) The monitor of claim 50, wherein the LCD device further comprises a shield case covering the PCB.

52. (Previously Presented) A liquid crystal display device comprising:

AB-1663 US
S.N. 09/850,367

a display unit;
a bottom chassis receiving the display unit;
a mold frame receiving the bottom chassis and having an opening exposing a bottom surface of the bottom chassis; and
a printed circuit board having a bottom surface attached directly to the bottom surface of the bottom chassis, the printed circuit board being disposed outside the mold frame.